

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) No 453/2010

Article No.: 22380000B  
Print date: 04.03.2019  
Version: 1.0

LUKAS-MALMITTEL 7  
Revision date: 04.03.2019  
Issue date: 04.03.2019

EN  
Page: 1 / 10

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. product identifiers

Article No. (manufacturer/supplier): 22380000B  
Identification of the substance or mixture LUKAS-MALMITTEL 7

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Relevant identified uses:

Artists supply and hobby preparations  
Coatings and paints, thinners, paint removers

### 1.3. Details of the supplier of the safety data sheet

#### Supplier (manufacturer/importer/downstream user/distributor):

Daler-Rowney Ltd  
Peacock Lane  
Bracknell, RG12 8SS  
ENGLAND  
Telephone: +44 (0) 1344 461083  
Telefax: +44 (0) 1344 486511

#### Dept. responsible for information:

E-mail Philip.Gray@daler-rowney.com

### 1.4. Emergency telephone number

Emergency telephone: +44 (0) 1344 461000

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 3 / H226	Flammable liquids	Flammable liquid and vapour.
Eye Dam. 1 / H318	Serious eye damage/eye irritation	Causes serious eye damage.
STOT SE 3 / H336	Specific target organ toxicity (single exposure)	May cause drowsiness or dizziness.
Aquatic Chronic 3 / H412	Hazardous to the aquatic environment	Harmful to aquatic life with long lasting effects.

### 2.2. Label elements

The product is classified and labelled according to EC directives or corresponding national laws.

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

#### Hazard pictograms



**Danger**

#### Hazard statements

H226 Flammable liquid and vapour.  
H318 Causes serious eye damage.  
H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.

#### Precautionary statements

P102 Keep out of the reach of children.  
P261 Avoid breathing vapours.  
P273 Avoid release to the environment.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 Immediately call a POISON CENTER or doctor/ physician.  
P262 Do not get in eyes, on skin, or on clothing.

#### contains:

Ethoxylated Nonylphneol  
1-methoxy-2-propanol

#### Supplemental Hazard information (EU)

EUH208 Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) No 453/2010

Article No.: 22380000B  
Print date: 04.03.2019  
Version: 1.0

LUKAS-MALMITTEL 7  
Revision date: 04.03.2019  
Issue date: 04.03.2019

EN  
Page: 2 / 10

## 2.3. Other hazards

### SECTION 3: Composition / information on ingredients

#### 3.2. Mixtures

##### Product description / chemical characterization

**Description** Painting Medium for Oil-Colour

##### Hazardous ingredients

##### Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No. CAS No. INDEX No.	REACH No. Chemical name classification:	Wt % Remark
203-539-1 107-98-2 603-064-00-3	1-methoxy-2-propanol Flam. Liq. 3 H226 / STOT SE 3 H336	25 - 50
918-668-5 649-356-00-4	01-2119455851-35-xxxx Hydrocarbons, C9, aromatics STOT SE 3 H335 / STOT SE 3 H336 / Asp. Tox. 1 H304 / Aquatic Chronic 2 H411 / Flam. Liq. 3 H226	12,5 - 20
216-374-5 1569-02-4 603-177-00-8	1-ethoxypropan-2-ol Flam. Liq. 3 H226 / STOT SE 3 H336	5 - 10
500-024-6 9016-45-9	Ethoxylated Nonylphneol Acute Tox. 4 H302 / Eye Dam. 1 H318 / Aquatic Chronic 2 H411	5 - 10
9016-45-9	Nonyl Phenol Ethoxylate Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / Aquatic Chronic 2 H411	2,5 - 5
68511-37-5	Mono-, di-, tri-(C12-C14-alkyl polyethylene glycol etherr) orthophosphate ester Skin Irrit. 2 H315	2,5 - 5
204-709-8 124-68-5 603-070-00-6	2119475788-16-0000 2-amino-2-methylpropanol Skin Irrit. 2 H315 / Eye Dam. 1 H318 / Aquatic Chronic 3 H412	1 - 2,5
220-120-9 2634-33-5 613-088-00-6	1,2-benzisothiazol-3(2H)-one Acute Tox. 4 H302 / Acute Tox. 2 H330 / Skin Irrit. 2 H315 / Eye Dam. 1 H318 / Skin Sens. 1 H317 / Aquatic Acute 1 H400 (M = 1) / Aquatic Chronic 2 H411	< 0,5

##### Additional information

Full text of classification: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

##### In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

##### Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

##### After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

##### After ingestion

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) No 453/2010

Article No.: 22380000B  
Print date: 04.03.2019  
Version: 1.0

LUKAS-MALMITTEL 7  
Revision date: 04.03.2019  
Issue date: 04.03.2019

EN  
Page: 3 / 10

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

#### 4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

#### 4.3. Indication of any immediate medical attention and special treatment needed

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

##### Extinguishing media which must not be used for safety reasons:

strong water jet

#### 5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage. Vapours form explosive mixtures with air.

#### 5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways. Cool closed containers that are near the source of the fire.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations. Vapours form explosive mixtures with air.

#### 6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

#### 6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

##### Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

##### Precautions against fire and explosion:

Vapours are heavier than air. Vapours form explosive mixtures with air.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSIVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (BGR 132)".

##### Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

##### Further information on storage conditions

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) No 453/2010

Article No.: 22380000B  
Print date: 04.03.2019  
Version: 1.0

LUKAS-MALMITTEL 7  
Revision date: 04.03.2019  
Issue date: 04.03.2019

EN  
Page: 4 / 10

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

### 7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limit values:

1-methoxy-2-propanol

INDEX No. 603-064-00-3 / EC No. 203-539-1 / CAS No. 107-98-2

TWA: 375 mg/m<sup>3</sup>; 100 ppm

STEL: 560 mg/m<sup>3</sup>; 150 ppm

#### Additional information

TWA : long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

#### DNEL:

1-methoxy-2-propanol

INDEX No. 603-064-00-3 / EC No. 203-539-1 / CAS No. 107-98-2

DNEL long-term dermal (systemic), Workers: 50.6 mg/kg

DNEL acute inhalative (local), Workers: 553.5 mg/m<sup>3</sup>

DNEL long-term inhalative (systemic), Workers: 369 mg/m<sup>3</sup>

DNEL long-term dermal (systemic), Consumer: 18.1 mg/kg

DNEL long-term inhalative (systemic), Consumer: 43.9 mg/m<sup>3</sup>

Hydrocarbons, C9, aromatics

INDEX No. 649-356-00-4 / EC No. 918-668-5

DNEL long-term dermal (systemic), Workers: 25 mg/kg

DNEL long-term inhalative (systemic), Workers: 150 mg/m<sup>3</sup>

DNEL long-term oral (repeated), Consumer: 11 mg/kg

DNEL long-term dermal (local), Consumer: 11 mg/kg

DNEL acute inhalative (local), Consumer: 32 mg/m<sup>3</sup>

#### PNEC:

1-methoxy-2-propanol

INDEX No. 603-064-00-3 / EC No. 203-539-1 / CAS No. 107-98-2

PNEC aquatic, freshwater: 10 mg/l

PNEC aquatic, marine water: 1 mg/l

PNEC sediment, freshwater: 41.6 mg/kg

PNEC sediment, marine water: 4.17 mg/kg

PNEC sewage treatment plant (STP): 100 mg/l

### 8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

#### Occupational exposure controls

##### Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

##### Hand protection

For prolonged or repeated handling the following glove material must be used:

Thickness of the glove material > 0,4 mm ; Breakthrough time (maximum wearing time) > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

##### Eye protection

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) No 453/2010

Article No.: 22380000B  
Print date: 04.03.2019  
Version: 1.0

LUKAS-MALMITTEL 7  
Revision date: 04.03.2019  
Issue date: 04.03.2019

EN  
Page: 5 / 10

Wear closely fitting protective glasses in case of splashes.

### Protective clothing

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

### Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

### Environmental exposure controls

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**Appearance:** Liquid  
**Physical state:** Liquid  
**Colour:** refer to label  
**Odour:** characteristic

#### Safety relevant basis data

	Unit	Method	Remark
Flash point:	32 °C	DIN 53213	
Ignition temperature in °C:	250 °C		
Lower explosion limit:	0,7 Vol-%		
Upper explosion limit:	12 Vol-%		
Vapour pressure at 20 °C::	90,8642		
Density at 20 °C::	1,00 g/cm <sup>3</sup>		
Water solubility (g/L):	partially soluble		
pH at 20 °C::	-		
Viscosity at 20 °C::	64 s 3 mm	EN ISO 2431	
Solvent separation test (%):	< 3 %		
boiling point in °C at 101,3 kPa	100 °C		

### 9.2. Other information:

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

### 10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

### 10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions. Vapours form explosive mixtures with air.

### 10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

### 10.5. Incompatible materials

### 10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

## SECTION 11: Toxicological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

No data on preparation itself available.

### 11.1. Information on toxicological effects

#### Acute toxicity

Nonyl Phenol Ethoxylate  
oral, LD50, Rat: > 2000 mg/kg

Ethoxylated Nonylphenol  
oral, LD50, Rat 500 - 2000 mg/kg

2-amino-2-methylpropanol  
oral, LD50, Rat: 2150 mg/kg  
dermal, LD50, Rabbit: > 2000 mg/kg

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) No 453/2010

Article No.: 22380000B  
Print date: 04.03.2019  
Version: 1.0

LUKAS-MALMITTEL 7  
Revision date: 04.03.2019  
Issue date: 04.03.2019

EN  
Page: 6 / 10

1-methoxy-2-propanol  
oral, LD50, Rat: 4016 mg/kg  
dermal, LD50, Rabbit: 2000 mg/kg

1,2-benzisothiazol-3(2H)-one  
oral, LD50, Rat: > 2000 mg/kg

1-ethoxypropan-2-ol  
oral, LD50, Rat: 4400 mg/kg  
dermal, LD50, Rabbit: 8100 mg/kg  
inhalative (vapours), LC50, Rat: 42.6 mg/l (4 h)

Mono-, di-, tri-(C12-C14-alkyl polyethylene glycol etherr) orthophosphate ester  
oral, LD50, Rat: > 2000 mg/kg

Hydrocarbons, C9, aromatics  
oral, LD50, Rat: 3592 mg/kg  
dermal, LD50, Rat: > 3160 mg/kg  
inhalative (vapours), LC50, Rat: > 10.2 mg/l (4 h)

## skin corrosion/irritation; Serious eye damage/eye irritation

Causes serious eye damage.

Nonyl Phenol Ethoxylate  
Skin, Rabbit  
Irritating to skin.  
eyes, Rabbit  
Irritating to eyes.

Ethoxylated Nonylphenol  
Skin, Rabbit. (4 h)  
Method: OECD 404  
Not an irritant.  
eyes, Rabbit.  
Method: OECD 405  
Risk of serious damage to eyes.

2-amino-2-methylpropanol  
Skin (4 h)  
Causes skin irritation.; Causes burns.  
eyes: evaluation Risk of serious damage to eyes.

Mono-, di-, tri-(C12-C14-alkyl polyethylene glycol etherr) orthophosphate ester  
Skin, OECD 404, Rabbit (4 h)  
irritant.  
eyes, OECD 405, Rabbit  
Not an irritant.

## Respiratory or skin sensitisation

Mono-, di-, tri-(C12-C14-alkyl polyethylene glycol etherr) orthophosphate ester  
Skin, OECD 406, Guinea pig:  
not sensitising.

## Specific target organ toxicity

May cause drowsiness or dizziness.

## Aspiration hazard

Toxicological data are not available.

## Practical experience/human evidence

Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

## Overall Assessment on CMR properties

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) No 453/2010

Article No.: 22380000B  
Print date: 04.03.2019  
Version: 1.0

LUKAS-MALMITTEL 7  
Revision date: 04.03.2019  
Issue date: 04.03.2019

EN  
Page: 7 / 10

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

## Remark

There is no information available on the preparation itself .

## SECTION 12: Ecological information

### overall evaluation

Classification according to Regulation (EC) No 1272/2008 [CLP]

There is no information available on the preparation itself .

Do not allow to enter into surface water or drains.

### 12.1. Toxicity

Nonyl Phenol Ethoxylate

Bacteria toxicity, EC50: 600 mg/l

Method: Fermentation tube test

Ethoxylated Nonylphneol

Fish toxicity, LC50: 6 mg/l (96 h)

Daphnia toxicity, EC50, Daphnia magna (Big water flea) 12.2 - 17 mg/l (48 h)

2-amino-2-methylpropanol

Fish toxicity, LC50, fish: 190 mg/l (96 h)

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 193 mg/l (48 h)

1-methoxy-2-propanol

Fish toxicity, LC50, Leuciscus idus (golden orfe): 6812 mg/l (96 h)

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 23300 mg/l (48 h)

1-ethoxypropan-2-ol

Fish toxicity, LC50, Pimephales promelas (fathead minnow): > 0 mg/l (96 h)

Hydrocarbons, C9, aromatics

Fish toxicity, LC50, fish 1 - 10 mg/l (96 h)

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 3.2 mg/l (48 h)

### Long-term Ecotoxicity

Harmful to aquatic life with long lasting effects.

Nonyl Phenol Ethoxylate

Fish toxicity, LC50 (96 h)

Ethoxylated Nonylphneol

Fish toxicity, LC50, Brachydanio rerio (zebra-fish) 1 - 10 mg/l (96 h)

Method: OECD 203

2-amino-2-methylpropanol

Fish toxicity, LC50, fish: 190 mg/l (96 h)

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 193 mg/l (48 h)

Algae toxicity, ErC50: 520 mg/l (96 h)

Hydrocarbons, C9, aromatics

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): 9.2 mg/l (96 h)

Fish toxicity, NOEC, Oncorhynchus mykiss (Rainbow trout): 1.23 mg/l (28 D)

Algae toxicity, NOEC, Daphnia magna (Big water flea): 2.14 mg/l (21 D)

### 12.2. Persistence and degradability

Ethoxylated Nonylphneol

: 86 % ; evaluation Readily biodegradable (according to OECD criteria).

2-amino-2-methylpropanol

Biodegradation: 89.3 % (28 D); evaluation Readily biodegradable (according to OECD criteria).

Method: OECD 301 F

1-ethoxypropan-2-ol

: 88 % (28 D)

Hydrocarbons, C9, aromatics

:

Photo-chemical elimination

### 12.3. Bioaccumulative potential

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) No 453/2010

Article No.: 22380000B  
Print date: 04.03.2019  
Version: 1.0

LUKAS-MALMITTEL 7  
Revision date: 04.03.2019  
Issue date: 04.03.2019

EN  
Page: 8 / 10

2-amino-2-methylpropanol

Partition coefficient: n-octanol/water: -0.63

Method: OECD 107

1-methoxy-2-propanol

Partition coefficient: n-octanol/water: -0.44

Method: Log KOC

1,2-benzisothiazol-3(2H)-one

Partition coefficient: n-octanol/water: 0.7

Method: OECD 117

Hydrocarbons, C9, aromatics

Partition coefficient: n-octanol/water: 3.7 - 6.7

## Bioconcentration factor (BCF)

1,2-benzisothiazol-3(2H)-one

Bioconcentration factor (BCF), fish: 6.95

Method: OECD 305

## 12.4. Mobility in soil

Toxicological data are not available.

## 12.5. Results of PBT assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## 12.6. Other adverse effects

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

#### List of proposed waste codes/waste designations in accordance with EWC

140603\* other solvents and solvent mixtures

#### packaging

#### Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste. Send to a collecting point for used paints.

## SECTION 14: Transport information

### 14.1. UN number

UN 1993

### 14.2. UN proper shipping name

Land transport (ADR/RID):

Flammable liquid, n.o.s.

(1-methoxy-2-propanole)

Sea transport (IMDG):

FLAMMABLE LIQUID, N.O.S.

(1-methoxy-2-propanole)

Air transport (ICAO-TI / IATA-DGR):

Flammable liquid, n.o.s.

(1-methoxy-2-propanole)

### 14.3. Transport hazard class(es)

3

### 14.4. Packing group

III

### 14.5. Environmental hazards

Land transport (ADR/RID)

not applicable

Marine pollutant

not applicable

### 14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) No 453/2010

Article No.: 22380000B  
Print date: 04.03.2019  
Version: 1.0

LUKAS-MALMITTEL 7  
Revision date: 04.03.2019  
Issue date: 04.03.2019

EN  
Page: 9 / 10

Advices on safe handling: see parts 6 - 8

## Further information

### Land transport (ADR/RID)

tunnel restriction code D/E

### Sea transport (IMDG)

EmS-No. F-E, S-E

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU legislation

#### Information according to 1999/13/EC about limitation of emissions of volatile organic compounds (VOC-guideline).

VOC-value (in g/L) ISO 11890-2: 457

VOC-value (in g/L) ASTM D 2369: 573

#### National regulations

#### Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

#### Other regulations, restrictions and prohibition regulations

### 15.2. Chemical Safety Assessment

For the following substances of this preparation a chemical safety assessment has been carried out:

EC No. CAS No.	Chemical name	REACH No.
204-709-8 124-68-5	2-amino-2-methylpropanol	2119475788-16-0000

## SECTION 16: Other information

### Full text of classification in section 3:

Flam. Liq. 3 / H226	Flammable liquids	Flammable liquid and vapour.
STOT SE 3 / H336	Specific target organ toxicity (single exposure)	May cause drowsiness or dizziness.
STOT SE 3 / H335	Specific target organ toxicity (single exposure)	May cause respiratory irritation.
Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.
Acute Tox. 4 / H302	Acute toxicity (oral)	Harmful if swallowed.
Eye Dam. 1 / H318	Serious eye damage/eye irritation	Causes serious eye damage.
Skin Irrit. 2 / H315	skin corrosion/irritation	Causes skin irritation.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
Aquatic Chronic 3 / H412	Hazardous to the aquatic environment	Harmful to aquatic life with long lasting effects.
Acute Tox. 2 / H330	Acute toxicity (inhalative)	Fatal if inhaled.
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.
Aquatic Acute 1 / H400	Hazardous to the aquatic environment	Very toxic to aquatic organisms.

### Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

### Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) No 453/2010

Article No.: 22380000B  
Print date: 04.03.2019  
Version: 1.0

LUKAS-MALMITTEL 7  
Revision date: 04.03.2019  
Issue date: 04.03.2019

EN  
Page: 10 / 10

---