

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010

Article No.: 22330000BB
Print date: 04.03.2019
Version: 1.0

LUKAS-MALMITTEL 6
Revision date: 04.03.2019
Issue date: 04.03.2019

EN
Page: 1 / 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. product identifiers

Article No. (manufacturer/supplier): 22330000BB
Identification of the substance or mixture LUKAS-MALMITTEL 6

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Artists supply and hobby preparations
Coatings and paints, thinners, paint removers

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/downstream user/distributor):

Daler-Rowney Ltd
Peacock Lane
Bracknell, RG12 8SS
ENGLAND
Telephone: +44 (0) 1344 461083
Telefax: +44 (0) 1344 486511

Dept. responsible for information:

E-mail Philip.Gray@daler-rowney.com

1.4. Emergency telephone number

Emergency telephone: +44 (0) 1344 461000

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 3 / H226	Flammable liquids	Flammable liquid and vapour.
Eye Dam. 1 / H318	Serious eye damage/eye irritation	Causes serious eye damage.
STOT SE 3 / H336	Specific target organ toxicity (single exposure)	May cause drowsiness or dizziness.
Aquatic Chronic 3 / H412	Hazardous to the aquatic environment	Harmful to aquatic life with long lasting effects.

2.2. Label elements

The product is classified and labelled according to EC directives or corresponding national laws.

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Danger

Hazard statements

H226 Flammable liquid and vapour.
H318 Causes serious eye damage.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of the reach of children.
P261 Avoid breathing vapours.
P273 Avoid release to the environment.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER or doctor/ physician.
P501 Dispose of contents/container in accordance with local legislation.
P262 Do not get in eyes, on skin, or on clothing.

contains:

Ethoxylated Nonylphneol
1-methoxy-2-propanol

Supplemental Hazard information (EU)

EUH208 Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010

Article No.: 22330000BB
Print date: 04.03.2019
Version: 1.0

LUKAS-MALMITTEL 6
Revision date: 04.03.2019
Issue date: 04.03.2019

EN
Page: 2 / 10

2.3. Other hazards

SECTION 3: Composition / information on ingredients

3.2. Mixtures

Product description / chemical characterization

Description Painting Medium for Oil-Colour

Hazardous ingredients

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No. CAS No. INDEX No.	REACH No. Chemical name classification:	Wt % Remark
203-539-1 107-98-2 603-064-00-3	1-methoxy-2-propanol Flam. Liq. 3 H226 / STOT SE 3 H336	12,5 - 20
918-668-5 649-356-00-4	01-2119455851-35-xxxx Hydrocarbons, C9, aromatics STOT SE 3 H335 / STOT SE 3 H336 / Asp. Tox. 1 H304 / Aquatic Chronic 2 H411 / Flam. Liq. 3 H226	10 - 12,5
216-374-5 1569-02-4 603-177-00-8	1-ethoxypropan-2-ol Flam. Liq. 3 H226 / STOT SE 3 H336	10 - 12,5
500-024-6 9016-45-9	Ethoxylated Nonylphneol Acute Tox. 4 H302 / Eye Dam. 1 H318 / Aquatic Chronic 2 H411	5 - 10
9016-45-9	Nonyl Phenol Ethoxylate Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / Aquatic Chronic 2 H411	2,5 - 5
68511-37-5	Mono-, di-, tri-(C12-C14-alkyl polyethylene glycol etherr) orthophosphate ester Skin Irrit. 2 H315	2,5 - 5
204-709-8 124-68-5 603-070-00-6	2119475788-16-0000 2-amino-2-methylpropanol Skin Irrit. 2 H315 / Eye Dam. 1 H318 / Aquatic Chronic 3 H412	1 - 2,5
220-120-9 2634-33-5 613-088-00-6	1,2-benzisothiazol-3(2H)-one Acute Tox. 4 H302 / Acute Tox. 2 H330 / Skin Irrit. 2 H315 / Eye Dam. 1 H318 / Skin Sens. 1 H317 / Aquatic Acute 1 H400 (M = 1) / Aquatic Chronic 2 H411	< 0,5

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010

Article No.: 22330000BB
Print date: 04.03.2019
Version: 1.0

LUKAS-MALMITTEL 6
Revision date: 04.03.2019
Issue date: 04.03.2019

EN
Page: 3 / 10

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Extinguishing media which must not be used for safety reasons:

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage. Vapours form explosive mixtures with air.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways. Cool closed containers that are near the source of the fire.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations. Vapours form explosive mixtures with air.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Precautions against fire and explosion:

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSIVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (BGR 132)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010

Article No.: 22330000BB
Print date: 04.03.2019
Version: 1.0

LUKAS-MALMITTEL 6
Revision date: 04.03.2019
Issue date: 04.03.2019

EN
Page: 4 / 10

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values:

1-methoxy-2-propanol

INDEX No. 603-064-00-3 / EC No. 203-539-1 / CAS No. 107-98-2

TWA: 375 mg/m³; 100 ppm

STEL: 560 mg/m³; 150 ppm

Additional information

TWA : long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

DNEL:

1-methoxy-2-propanol

INDEX No. 603-064-00-3 / EC No. 203-539-1 / CAS No. 107-98-2

DNEL long-term dermal (systemic), Workers: 50.6 mg/kg

DNEL acute inhalative (local), Workers: 553.5 mg/m³

DNEL long-term inhalative (systemic), Workers: 369 mg/m³

DNEL long-term dermal (systemic), Consumer: 18.1 mg/kg

DNEL long-term inhalative (systemic), Consumer: 43.9 mg/m³

Hydrocarbons, C9, aromatics

INDEX No. 649-356-00-4 / EC No. 918-668-5

DNEL long-term dermal (systemic), Workers: 25 mg/kg

DNEL long-term inhalative (systemic), Workers: 150 mg/m³

DNEL long-term oral (repeated), Consumer: 11 mg/kg

DNEL long-term dermal (local), Consumer: 11 mg/kg

DNEL acute inhalative (local), Consumer: 32 mg/m³

PNEC:

1-methoxy-2-propanol

INDEX No. 603-064-00-3 / EC No. 203-539-1 / CAS No. 107-98-2

PNEC aquatic, freshwater: 10 mg/l

PNEC aquatic, marine water: 1 mg/l

PNEC sediment, freshwater: 41.6 mg/kg

PNEC sediment, marine water: 4.17 mg/kg

PNEC sewage treatment plant (STP): 100 mg/l

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Occupational exposure controls

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used:

Thickness of the glove material > 0,4 mm ; Breakthrough time (maximum wearing time) > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye protection

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010

Article No.: 22330000BB
Print date: 04.03.2019
Version: 1.0

LUKAS-MALMITTEL 6
Revision date: 04.03.2019
Issue date: 04.03.2019

EN
Page: 5 / 10

Wear closely fitting protective glasses in case of splashes.

Protective clothing

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance: Liquid
Physical state: Liquid
Colour: refer to label
Odour: characteristic

Safety relevant basis data

	Unit	Method	Remark
Flash point:	33 °C	DIN 53213	
Ignition temperature in °C:	250 °C		
Lower explosion limit:	0,7 Vol-%		
Upper explosion limit:	12 Vol-%		
Vapour pressure at 20 °C::	89,523		
Density at 20 °C::	1,00 g/cm ³		
Water solubility (g/L):	partially soluble		
pH at 20 °C::	-		
Viscosity at 20 °C::	161 s 3 mm	EN ISO 2431	
Solvent separation test (%):	< 3 %		
boiling point in °C at 101,3 kPa	100 °C		

9.2. Other information:

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions. Vapours form explosive mixtures with air.

10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

No data on preparation itself available.

11.1. Information on toxicological effects

Acute toxicity

Nonyl Phenol Ethoxylate
oral, LD50, Rat: > 2000 mg/kg

Ethoxylated Nonylphenol
oral, LD50, Rat 500 - 2000 mg/kg

2-amino-2-methylpropanol
oral, LD50, Rat: 2150 mg/kg
dermal, LD50, Rabbit: > 2000 mg/kg

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010

Article No.: 22330000BB
Print date: 04.03.2019
Version: 1.0

LUKAS-MALMITTEL 6
Revision date: 04.03.2019
Issue date: 04.03.2019

EN
Page: 6 / 10

1-methoxy-2-propanol
oral, LD50, Rat: 4016 mg/kg
dermal, LD50, Rabbit: 2000 mg/kg

1,2-benzisothiazol-3(2H)-one
oral, LD50, Rat: > 2000 mg/kg

1-ethoxypropan-2-ol
oral, LD50, Rat: 4400 mg/kg
dermal, LD50, Rabbit: 8100 mg/kg
inhalative (vapours), LC50, Rat: 42.6 mg/l (4 h)

Mono-, di-, tri-(C12-C14-alkyl polyethylene glycol etherr) orthophosphate ester
oral, LD50, Rat: > 2000 mg/kg

Hydrocarbons, C9, aromatics
oral, LD50, Rat: 3592 mg/kg
dermal, LD50, Rat: > 3160 mg/kg
inhalative (vapours), LC50, Rat: > 10.2 mg/l (4 h)

skin corrosion/irritation; Serious eye damage/eye irritation

Causes serious eye damage.

Nonyl Phenol Ethoxylate
Skin, Rabbit
Irritating to skin.
eyes, Rabbit
Irritating to eyes.

Ethoxylated Nonylphenol
Skin, Rabbit. (4 h)
Method: OECD 404
Not an irritant.
eyes, Rabbit.
Method: OECD 405
Risk of serious damage to eyes.

2-amino-2-methylpropanol
Skin (4 h)
Causes skin irritation.; Causes burns.
eyes: evaluation Risk of serious damage to eyes.

Mono-, di-, tri-(C12-C14-alkyl polyethylene glycol etherr) orthophosphate ester
Skin, OECD 404, Rabbit (4 h)
irritant.
eyes, OECD 405, Rabbit
Not an irritant.

Respiratory or skin sensitisation

Mono-, di-, tri-(C12-C14-alkyl polyethylene glycol etherr) orthophosphate ester
Skin, OECD 406, Guinea pig:
not sensitising.

Specific target organ toxicity

May cause drowsiness or dizziness.

Aspiration hazard

Toxicological data are not available.

Practical experience/human evidence

Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010

Article No.: 22330000BB
Print date: 04.03.2019
Version: 1.0

LUKAS-MALMITTEL 6
Revision date: 04.03.2019
Issue date: 04.03.2019

EN
Page: 7 / 10

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Remark

There is no information available on the preparation itself .

SECTION 12: Ecological information

overall evaluation

Classification according to Regulation (EC) No 1272/2008 [CLP]

There is no information available on the preparation itself .

Do not allow to enter into surface water or drains.

12.1. Toxicity

Nonyl Phenol Ethoxylate

Bacteria toxicity, EC50: 600 mg/l

Method: Fermentation tube test

Ethoxylated Nonylphneol

Fish toxicity, LC50: 6 mg/l (96 h)

Daphnia toxicity, EC50, Daphnia magna (Big water flea) 12.2 - 17 mg/l (48 h)

2-amino-2-methylpropanol

Fish toxicity, LC50, fish: 190 mg/l (96 h)

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 193 mg/l (48 h)

1-methoxy-2-propanol

Fish toxicity, LC50, Leuciscus idus (golden orfe): 6812 mg/l (96 h)

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 23300 mg/l (48 h)

1-ethoxypropan-2-ol

Fish toxicity, LC50, Pimephales promelas (fathead minnow): > 0 mg/l (96 h)

Hydrocarbons, C9, aromatics

Fish toxicity, LC50, fish 1 - 10 mg/l (96 h)

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 3.2 mg/l (48 h)

Long-term Ecotoxicity

Harmful to aquatic life with long lasting effects.

Nonyl Phenol Ethoxylate

Fish toxicity, LC50 (96 h)

Ethoxylated Nonylphneol

Fish toxicity, LC50, Brachydanio rerio (zebra-fish) 1 - 10 mg/l (96 h)

Method: OECD 203

2-amino-2-methylpropanol

Fish toxicity, LC50, fish: 190 mg/l (96 h)

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 193 mg/l (48 h)

Algae toxicity, ErC50: 520 mg/l (96 h)

Hydrocarbons, C9, aromatics

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): 9.2 mg/l (96 h)

Fish toxicity, NOEC, Oncorhynchus mykiss (Rainbow trout): 1.23 mg/l (28 D)

Algae toxicity, NOEC, Daphnia magna (Big water flea): 2.14 mg/l (21 D)

12.2. Persistence and degradability

Ethoxylated Nonylphneol

: 86 % ; evaluation Readily biodegradable (according to OECD criteria).

2-amino-2-methylpropanol

Biodegradation: 89.3 % (28 D); evaluation Readily biodegradable (according to OECD criteria).

Method: OECD 301 F

1-ethoxypropan-2-ol

: 88 % (28 D)

Hydrocarbons, C9, aromatics

:

Photo-chemical elimination

12.3. Bioaccumulative potential

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010

Article No.: 22330000BB
Print date: 04.03.2019
Version: 1.0

LUKAS-MALMITTEL 6
Revision date: 04.03.2019
Issue date: 04.03.2019

EN
Page: 8 / 10

2-amino-2-methylpropanol

Partition coefficient: n-octanol/water: -0.63

Method: OECD 107

1-methoxy-2-propanol

Partition coefficient: n-octanol/water: -0.44

Method: Log KOC

1,2-benzisothiazol-3(2H)-one

Partition coefficient: n-octanol/water: 0.7

Method: OECD 117

Hydrocarbons, C9, aromatics

Partition coefficient: n-octanol/water: 3.7 - 6.7

Bioconcentration factor (BCF)

1,2-benzisothiazol-3(2H)-one

Bioconcentration factor (BCF), fish: 6.95

Method: OECD 305

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

140603* other solvents and solvent mixtures

packaging

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste. Send to a collecting point for used paints.

SECTION 14: Transport information

14.1. UN number

UN 1993

14.2. UN proper shipping name

Land transport (ADR/RID):

Flammable liquid, n.o.s.
(Resin Solution)

Sea transport (IMDG):

FLAMMABLE LIQUID, N.O.S.
(Resin Solution)

Air transport (ICAO-TI / IATA-DGR):

Flammable liquid, n.o.s.
(Resin Solution)

14.3. Transport hazard class(es)

3

14.4. Packing group

III

14.5. Environmental hazards

Land transport (ADR/RID)

not applicable

Marine pollutant

not applicable

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010

Article No.: 22330000BB
Print date: 04.03.2019
Version: 1.0

LUKAS-MALMITTEL 6
Revision date: 04.03.2019
Issue date: 04.03.2019

EN
Page: 9 / 10

Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

tunnel restriction code D/E

Sea transport (IMDG)

EmS-No. F-E, S-E

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Information according to 1999/13/EC about limitation of emissions of volatile organic compounds (VOC-guideline).

VOC-value (in g/L) ISO 11890-2: 423

VOC-value (in g/L) ASTM D 2369: 511

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Other regulations, restrictions and prohibition regulations

15.2. Chemical Safety Assessment

For the following substances of this preparation a chemical safety assessment has been carried out:

EC No. CAS No.	Chemical name	REACH No.
204-709-8 124-68-5	2-amino-2-methylpropanol	2119475788-16-0000

SECTION 16: Other information

Full text of classification in section 3:

Flam. Liq. 3 / H226	Flammable liquids	Flammable liquid and vapour.
STOT SE 3 / H336	Specific target organ toxicity (single exposure)	May cause drowsiness or dizziness.
STOT SE 3 / H335	Specific target organ toxicity (single exposure)	May cause respiratory irritation.
Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.
Acute Tox. 4 / H302	Acute toxicity (oral)	Harmful if swallowed.
Eye Dam. 1 / H318	Serious eye damage/eye irritation	Causes serious eye damage.
Skin Irrit. 2 / H315	skin corrosion/irritation	Causes skin irritation.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
Aquatic Chronic 3 / H412	Hazardous to the aquatic environment	Harmful to aquatic life with long lasting effects.
Acute Tox. 2 / H330	Acute toxicity (inhalative)	Fatal if inhaled.
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.
Aquatic Acute 1 / H400	Hazardous to the aquatic environment	Very toxic to aquatic organisms.

Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010

Article No.: 22330000BB
Print date: 04.03.2019
Version: 1.0

LUKAS-MALMITTEL 6
Revision date: 04.03.2019
Issue date: 04.03.2019

EN
Page: 10 / 10
